



**NOTE:**

**ELECTRICAL:**

- 1. VOLTAGE RATING : 125 VAC RMS
- 2. CURRENT RATING : 1.5 AMP
- 3. CONTACT RESISTANCE : 300 MILLI OHMS MAX
- 4. INSULATION RESISTANCE : 1000M OHMS MIN @ 500V DC
- 5. DIELECTRIC STRENGTH : 750V AC RMS 60Hz, 1MIN
- 6. CAT. 6 PERMANENT LINK : CONFORM TO ANSI/TIA/EIA-568 B.2-1

**ENVIRONMENTAL:**

- 1. STORAGE : -40° TO+85°
  - 2. OPERATION : 0° TO+70°
- MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68

**MECHANICAL**

- 1. HOUSING MATERIAL PBT+15%GF UL94V0
- 2. PANEL FRAME S45C. POWDER COATING
- 3. IDC MATERIAL: PC UL94V0 TERMINAL:PHOSPHOR BRONZE, TIN PLATING
- 4. RJ45 JACK LIFE: 750 TIMES MIN
- 5. IDC LIFE : 200 TIMES MIN
- 6. RETENTIVENESS OF INSERTION STRUCTURE: 50N 60±5s

**Accessory:**

- 1. Cable Tie(75X1.9mm) ×4Pcs
- 2. Instruction Sheet
- 3. Screw M5\*12mm ×4pcs
- 4. Silica gel 3.5G ×1PCS

RoHS 2.0 + REACH COMPLIANT

Packing: 1pcs/panel box+1lable

ITEM NO.	Colour
	Gray RAL 7035
NP0041B	Black RAL 9005

**MATERIAL LIST:**

NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK
⑥	Front Panel	1.2mm thickness Metall Panel with plastic powder cladding	1	
⑤	RJ45 Jack	Housing-Fireproof PBT UL-94V0 Pin-8P8C 3u" gold plated	12	
④	PCB	1.6mm UL-94V0	3	
③	IDC Body	Fireproof PC/ABS UL-94V0	12	
②	IDC Pin	Phosphor Bronze & Tinned	96	
①	IDC Terminal	For 22-24 AWG Cable	24	

LogiLink Professional					
		2Direct Gmbh	ITEM NO.	see the chart	
PRODUCT NAME	CAT. 6 UTP 10" 12PORT PATCH PANEL Vertical version incl		UNIT	MM	
	NEW	2015-11-12	A	DRAWNBY	CHECKBY
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	APPOBY	DATE
			REV.		2015-11-12